

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
17 March 2005 (17.03.2005)

PCT

(10) International Publication Number  
**WO 2005/022981 A1**

(51) International Patent Classification<sup>7</sup>:  
3/08, 23/095 A01G 3/00,

[AU/AU]; 13 Alcheringa Place, Robertson, Queensland  
4109 (AU).

(21) International Application Number:  
PCT/AU2004/001193

(74) Agent: PIZZEYS PATENT AND TRADE MARK AT-  
TORNEYS; Level 14, ANZ Centre, 324 Queen Street,  
Brisbane, Queensland 4000 (AU).

(22) International Filing Date:  
3 September 2004 (03.09.2004)

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003904810 4 September 2003 (04.09.2003) AU

(71) Applicant (for all designated States except US): AUST  
PACIFIC FOREST MANAGEMENT PTY LTD  
[AU/AU]; 13 Alcheringa Place, Robertsins, Queensland  
4109 (AU).


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

(72) Inventor; and

(75) Inventor/Applicant (for US only): UEBERGANG, Collin

[Continued on next page]

(54) Title: TREE PRUNING APPARATUS



(57) Abstract: A pruning assembly (10) including an elongate supporting body (not shown), right (11) and left (12) jaw members hinged together and movable along the supporting body and each having three set of blade members (31) mounted on actuator means (16) and alternatively displaced above and below a plane to form two staggered rows of three bores each, the actuator means (16) adapted to maintain the clearance between the trunk and each set of blade members (31).

WO 2005/022981 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, — *with amended claims and statement*  
GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

5

## TREE PRUNING APPARATUS

This invention relates to tree pruning apparatus.

This invention has particular but not exclusive application to tree pruning apparatus for plantation forestry species such as *Pinus radiata* and especially high value species such as *Araucaria cunninghamii*, and for illustrative purposes  
10 reference will be made to such application. However, it is to be understood that this invention could be used in other applications, such as tree pruning other forestry species where excision of lower limbs is required to add value.

## PRIOR ART

In the farming of *Araucaria cunninghamii* (hoop pine) and other species  
15 there is a commercial advantage in pruning the lower branch sprouts to prevent them forming knots in the timber and to focus growth effort of the crown in to producing clear timber. As a manual task the pruning of trees is a labour intensive process. A mechanised means of pruning is thus of great commercial interest. An intuitive approach to tree pruning has been developed by CSIRO. This  
20 technology comprises an openable collar bearing hydraulically disposed chisel portions and operated by a hoisting mechanism to prune a forestry tree from the lower branches to branches at a selected height.

The disadvantages of this construction reside in the fact that the chisels are adjusted and fixed for the tree at the beginning of the stroke. Many species bud  
25 limbs from nodules on the extended trunk. In the case of hoop pine, the budding structures form the distinctive hoops that give the hoop pine its common name. The setting of the chisels must avoid the scalping of the bark at the hoops. However since trees generally taper from the base, the collar may be oversized for the upper limbs to avoid scalping lower down. The effective oversize for the upper  
30 limbs results in ineffective abscission of limbs higher up the trunk.

## BRIEF DESCRIPTION OF THE INVENTION

This invention in one aspect resides broadly in tree pruning apparatus including:

an elongate supporting body locatable alongside the trunk of a tree to be  
35 pruned;

5 a pruning assembly mounted on and drivable along said supporting body and comprising a plurality of pruning jaws movable from an open position and a closed position substantially encircling the trunk;

a plurality of blade members mounted on said jaws and having cutting edges forming a substantially circumferential array when said jaws are in their  
10 closed position; and

actuator means associated with each said blade member and adapted to dynamically maintain the clearance between the trunk and each said cutting edge.

In a further aspect his invention resides broadly in a tree pruning method including the steps of:

15 locating an elongate supporting body alongside the trunk of a tree to be pruned;

closing pruning jaws of a pruning assembly mounted on and drivable along said supporting body to substantially encircle the trunk, said jaws mounting a plurality of blade members having cutting edges forming a substantially  
20 circumferential array, the blade members being dynamically maintained as to clearance between the trunk and each said cutting edge by actuator means associated with each said blade member; and

driving said pruning assembly along said elongate supporting body to prune said tree.

## 25 DESCRIPTION OF INVENTION

The elongate supporting body may include a wheeled or tracked vehicle for locating the body adjacent the tree trunk. The vehicle may be a powered vehicle or may be hand operated. For example, the vehicle may be a gyro-stabilized horizontal transport platform. The elongate support body may mount the pruning  
30 assembly by any suitable means. For example the body member may be configured as a vertical track or chain along which the pruning assembly is captively mounted for rolling. The rolling pruning assembly may be urged along the vertical track by a chain drive, ram or hydraulic, pneumatic or electric motor.

The jaws of the pruning assembly may comprise a pair of jaws hinged  
35 together or each pivoted from a carrier portion engaging the pruning assembly with the elongate supporting body. Where the jaws are hinged together, one jaw may

5 be associated with the elongate support. The jaws may be operable by any suitable means such as manually or by hydraulic or pneumatic actuation.

The actuators for each of the blade members may be operable to maintain a selected clearance, preferably in the region of 4 to 10mm, by any suitable means. For example the actuators may comprise a mechanical sensor arm  
10 adapted to roll along the trunk below or above the blade and serves to control the positioning of the blade by limiting the extent to which the blade may move toward and away from the trunk. The actuator may be under the control of electronic or optoelectronic distance sensing means performing the same function.

The actuator may comprise an electric, pneumatic or hydraulic actuator.  
15 Preferably the actuator is a pneumatic actuator to utilize the elasticity of the working fluid. The use of pneumatic actuation comprising a spring/air actuator enables the apparatus to be operated at high speed whilst allowing some inherent compliance to reduce inertial "blocking". Thus for a given sensed position of the blade, rapid changes of section may be taken up in part by the compliance in the  
20 actuator to preserve limb nodules and other cambium-containing portions of the trunk whilst ensuring effective excision of the limbs. Thus suitable commercial fast-response pneumatic actuators may be fine tuned as to operating pressure, such as at pressures of 10 to 50 psi.

The selected dynamically maintained distance between the blades and the  
25 trunk will be selected having regard to the tree species, the nodule size and the response rate of the actuators. For example, for high speed operation on species with large nodules, the clearance may be set quite high.

It is particularly desirable to configure the apparatus for speed of operation that is quite high relative to the speed of operation of prior art apparatus. In  
30 practice it has been determined that apparatus of the present invention may be operated at a linear blade edge velocity of from 1 to 2.5 m/sec, the actual speed being selected to deliver the best compromise between blade positioning response rate and an axe-like chopping effect on the limbs to be excised.

Preferred embodiments of the invention utilize pneumatic sensor/actuators,  
35 where a spring biased blade member is urged toward the trunk against the spring by a pneumatic actuator which is continuously operable in response to a follower interacting with the tree trunk.

5           The blade members may have straight cutting edges or the cutting wedges may be arcuate such that at a best average disposition of the blade members the cutting edges describe in combination a substantially circular cutting edge in plan. Conventional wisdom would have the cutting edge of the blades being of chisel-edges form, that is, with a substantially sheer face toward the trunk and a bevel  
10       from the cutting edge to the thickness of the blade body. In fact this configuration does provide an appropriate blade for many tree species. However, it has been determined that for certain species a modest relief of the sheer face of the blade produces better results for certain species. For example it has been determined that for blade velocities of about 1.0 to 2.5 m/sec, relieving the edge by 6° from the  
15       sheer plane for hoop pine produces a cleaner shearing of the excised limbs, whereas no relief (0°) works for eucalypts and *P. radiata*.

          In forming the working circumference of the apparatus the blade members must have gaps between them to accommodate changes in adjusted size, if these are arrayed in a single circumferential plane. Limbs may fail to be sheared cleanly  
20       if they pass into a gap to be merely bruised or brushed aside by the supporting collar structure. Accordingly it is preferred that the blade members be arrayed in two or more planes with overlapping edges in plan. Accordingly in a further aspect this invention resides broadly in tree pruning apparatus including:

          an elongate supporting body locatable alongside the trunk of a tree to be  
25       pruned;

          a pruning assembly mounted on and drivable along said supporting body and comprising a plurality of pruning jaws movable from an open position and a closed position substantially encircling the trunk; and

          a plurality of blade members mounted on said jaws and having cutting  
30       edges in circumferentially overlapping relation when said jaws are in their closed position.

          In a further aspect his invention resides broadly in tree pruning method including the steps of:

          locating an elongate supporting body alongside the trunk of a tree to be  
35       pruned;

          closing pruning jaws of a pruning assembly mounted on and drivable along said supporting body to substantially encircle the trunk, said jaws mounting a plurality

5 of blade members having cutting edges in circumferentially overlapping relation;  
and  
driving said pruning assembly along said elongate supporting body to prune said  
tree.

The blade members may achieve the required circumferential overlap of  
10 extent of the cutting edges in use by means of being vertically staggered. For  
example the blade members may be disposed in two or more circumferential  
arrays stacked on the jaws, the arrays being offset in their circumferential  
disposition to present a substantially continuous cutting edge in plan. The blade  
members may have straight cutting edges or the cutting wedges may be arcuate  
15 such that at a best average disposition of the blade members the cutting edges  
describe in combination a substantially circular cutting edge in plan.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In order that this invention may be more readily understood and put into practical  
effect, reference will now be made to the accompanying drawings which illustrate  
20 a preferred embodiment of the invention and wherein:

FIG. 1 is a plan view of pruning apparatus in accordance with the present  
invention;

FIG. 2 is a detail view of a blade assembly for use with the apparatus of  
FIG. 1;

25 FIG.3 is a front perspective view of the apparatus of FIG. 1, inoperatively  
open;

FIG.4 is a rear perspective view of the apparatus of FIG. 1, inoperatively  
open; and

FIG.5 is a detail perspective view of a jaw of the apparatus of FIG. 1.

#### 30 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the figures, there is provided tree pruning apparatus having a pruning  
assembly 10 including right 11 and left 12 jaw members. The jaw members 11, 12  
are hinged together to a lift carriage (not shown) by a common pin 18 passing into  
bores 14. The jaw members 11 and 12 have substantially semicircular bodies 15  
35 and each have three actuator mounting bores 16 formed therein. At the ends of  
the jaw members 11, 12 remote from the bores 14 are respective stop portions 17

- 5 limiting the closure of the jaw members 11, 12. The jaw members in assembly are opened and closed by a double action actuator (not shown).

The six actuator mounting bores 16 in the assembly of the jaw members are alternately displaced above and below a plane to form two staggered rows of three bores each. Welded into the bores 16 are actuator housings 20 having  
10 controlled air supplies 21, a bias spring 22 and end caps 23. Mounted in the housings 20 and forming a part of the actuator are pistons 24 each forming part of a blade and gauge assembly 25 best illustrated in FIG. 2. The jaw members 11, 12 have a guide bore (not shown) located in spaced relation below each actuator mounting bore 16.

- 15 Each blade and gauge assembly 25 comprises a body member 26 welded to the piston 24 and a guide rod 27 welded to the body member 26 in spaced, parallel relation to the piston 24, the guide rod being adapted to engage for sliding in the corresponding guide bore of the jaw member 11 or 12. The upper end of the body member 26 is configured as a blade mounting portion 30 to which an  
20 arcuate blade 31 is secured by machine screws 32.

- The arcuate blade 31 is of circumferential extent such that in plan the respective blade edges of adjacent blades 31 overlap such as at the region 33 of FIG. 1. The cutting edge of the blade 31 is essentially a chisel edge with a bevel 34 and having a relief angle at the substantially sheer face of about 7° at 38. The  
25 bias springs 22 biases the body members 26 out from the tree in use, and whereby operation of the actuator urges the body members toward the tree in use.

- The body member 26 pivotally mounts a mechanical follower 35 at 36. The mechanical follower 35 has a contact face 37 adapted to follow the tree trunk and operating a transducer 40 outputting a relational signal to terminals 41. The signal  
30 output from the terminals 41 are used to operate control means (not shown), which in turn operated the air supplies 21 to dynamically adjust the blade clearance from the trunk for each actuator.

- Apparatus in accordance with the foregoing embodiment has the advantages that the blade clearance is constantly adjusted on installation of the  
35 jaw members about the tree and during the pruning action. The individual control of the clearance accommodates out-of-round trunks as well as maintaining the cutting distance. The overlapping plan of the blade edges prevents limbs from



- 5    passing between cutting edges, resulting in a cleanly pruned tree. The use of air actuators allows for reflexive adjustment in the face of inertia of the relatively heavy blade parts.

It will of course be realised that while the above has been given by way of illustrative example of this invention, all such and other modifications and variations thereto as would be apparent to persons skilled in the art are deemed to fall within the broad scope and ambit of this invention as defined in the claims appended hereto.

10

## 5 CLAIMS

1. Tree pruning apparatus including:
  - an elongate supporting body locatable along the trunk of a tree to be pruned;
  - a pruning assembly mounted on and drivable along said supporting body
  - 10 and comprising a plurality of pruning jaws movable from an open position and a closed position substantially encircling the trunk;
  - a plurality of blade members mounted on said jaws and having cutting edges forming a substantially circumferential array when said jaws are in their closed position; and
  - 15 actuator means associated with each said blade member and adapted to dynamically maintain the clearance between the trunk and each said cutting edge.
2. Tree pruning apparatus according to Claim 1, wherein said elongate supporting body is mounted on a wheeled or tracked vehicle for locating the body
- 20 adjacent the tree trunk.
3. Tree pruning apparatus according to Claim 1, wherein said vehicle is selected from powered and hand operated vehicles.
- 25 4. Tree pruning apparatus according to any one of Claims 1 to 3, wherein said elongate supporting body mounts said pruning assembly for movement by means selected from a track or moving chain.
5. Tree pruning apparatus according to Claim 4, wherein said pruning
- 30 assembly is urged along the vertical track by means selected from a chain drive, ram or hydraulic, pneumatic or electric motor.
6. Tree pruning apparatus according to any one of Claims 1 to 5, wherein said jaws of the pruning assembly comprise a pair of jaws hinged together.
- 35 7. Tree pruning apparatus according to Claim 6, wherein one said jaw is mounted for movement on said elongate supporting body.

5

8. Tree pruning apparatus according to any one of Claims 1 to 5, wherein said jaws are each pivoted from a carrier portion engaging said elongate supporting body.

10 9. Tree pruning apparatus according to any one of the preceding Claims, wherein said jaws are operable by means selected from manual means, hydraulic actuation and pneumatic actuation.

10. Tree pruning apparatus according to any one of the preceding Claims,  
15 wherein said actuator means for each of the blade members are operable to maintain a selected clearance under the control of sensor means.

11. Tree pruning apparatus according to Claim 10, wherein said sensor means comprises a mechanical sensor arm associated with the actuator means for each  
20 blade member and adapted to move along the trunk ahead of said blade member.

12. Tree pruning apparatus according to Claim 10, wherein said sensor means comprises electronic or optoelectronic distance sensing means associated with the actuator means for each blade member.

25

13. Tree pruning apparatus according to any one of the preceding Claims, wherein said actuator means are selected from electric, pneumatic or hydraulic actuators.

30 14. Tree pruning apparatus according to Claim 13, wherein said actuator means are pneumatic actuator assemblies comprising a pneumatic actuator working against a spring.

15. Tree pruning apparatus according to any one of the preceding Claims,  
35 wherein said pruning assembly is driven along said elongate body member in use at a linear blade edge velocity of from 1 to 2.5 m/sec.

5 16. Tree pruning apparatus according to Claim 14, wherein said pneumatic actuator and spring comprise a sensor/actuator assembly, wherein said blade member is urged toward the trunk against the bias of said spring by said pneumatic actuator which is continuously operable in response to a follower interacting with the tree trunk as said sensor.

10

17. Tree pruning apparatus according to any one of the preceding Claims, wherein said blade members have arcuate cutting edges.

18. Tree pruning apparatus according to Claim 17, wherein said cutting edges  
15 describe in combination a substantially circular cutting edge in plan.

19. Tree pruning apparatus according to Claim 17 or Claim 18, wherein said blade members are arrayed in two or more axially displaced planes, whereby said cutting edges may overlap in plan.

20

20. Tree pruning apparatus according to any one of the preceding Claims, wherein said blade members have a cutting edge of chisel-edged form with a substantially sheer face toward the trunk in use and a bevel from the cutting edge to the thickness of the blade body.

25

21. Tree pruning apparatus according to Claim 19, wherein said sheer face is relieved along said cutting edge at a relief angle of up to 6°.

22. A tree pruning method including the steps of:

30 locating an elongate supporting body alongside the trunk of a tree to be pruned;

closing pruning jaws of a pruning assembly mounted on and drivable along said supporting body to substantially encircle the trunk, said jaws mounting a plurality of blade members having cutting edges forming a substantially  
35 circumferential array, the blade members being dynamically maintained as to clearance between the trunk and each said cutting edge by actuator means associated with each said blade member; and

5 driving said pruning assembly along said elongate supporting body to prune said tree.

23. Tree pruning apparatus including:  
an elongate supporting body locatable alongside the trunk of a tree to be  
10 pruned;  
a pruning assembly mounted on and drivable along said supporting body and comprising a plurality of pruning jaws movable from an open position and a closed position substantially encircling the trunk; and  
a plurality of blade members mounted on said jaws and having cutting  
15 edges in circumferentially overlapping relation when said jaws are in their closed position.

24. A tree pruning method including the steps of:  
locating an elongate supporting body alongside the trunk of a tree to be  
20 pruned;  
closing pruning jaws of a pruning assembly mounted on and drivable along said supporting body to substantially encircle the trunk, said jaws mounting a plurality of blade members having cutting edges in circumferentially overlapping relation; and  
25 driving said pruning assembly along said elongate supporting body to prune said tree.

**AMENDED CLAIMS**

[received by the International Bureau on 14 December 2004 (14.12.04);  
original claims 1-24 replaced by new claims 1-23 (5 pages).]

1. Tree pruning apparatus including:  
an elongate supporting body locatable along the trunk of a tree to be pruned;  
5 a pruning assembly mounted on and drivable along said supporting body and comprising a plurality of pruning jaws movable from an open position and a closed position substantially encircling the trunk;  
a plurality of blade members mounted on said jaws and having cutting edges forming a substantially circumferential array when said jaws are in their  
10 closed position; and  
actuator means associated with each said blade member; and  
individual sensor means associated with each actuator means and operable to dynamically maintain a selected clearance between the trunk and each said cutting edge.  
15
2. Tree pruning apparatus according to Claim 1, wherein said elongate supporting body is mounted on a wheeled or tracked vehicle for locating the body adjacent the tree trunk.
- 20 3. Tree pruning apparatus according to Claim 1, wherein said vehicle is selected from powered and hand operated vehicles.
4. Tree pruning apparatus according to any one of Claims 1 to 3, wherein said elongate supporting body mounts said pruning assembly for movement by  
25 means selected from a track or moving chain.
5. Tree pruning apparatus according to Claim 4, wherein said pruning assembly is urged along the vertical track by means selected from a chain drive, ram or hydraulic, pneumatic or electric motor.  
30
6. Tree pruning apparatus according to any one of Claims 1 to 5, wherein said jaws of the pruning assembly comprise a pair of jaws hinged together.

7. Tree pruning apparatus according to Claim 6, wherein one said jaw is mounted for movement on said elongate supporting body.
- 5 8. Tree pruning apparatus according to any one of Claims 1 to 5, wherein said jaws are each pivoted from a carrier portion engaging said elongate supporting body.
9. Tree pruning apparatus according to any one of the preceding Claims,  
10 wherein said jaws are operable by means selected from manual means, hydraulic actuation and pneumatic actuation.
10. Tree pruning apparatus according to any one of the preceding Claims, wherein said sensor means comprises a mechanical sensor arm associated  
15 with the actuator means for each blade member and adapted to move along the trunk ahead of said blade member.
11. Tree pruning apparatus according to any one of the preceding Claims, wherein said sensor means comprises electronic or optoelectronic distance  
20 sensing means associated with the actuator means for each blade member.
12. Tree pruning apparatus according to any one of the preceding Claims, wherein said actuator means are selected from electric, pneumatic or hydraulic  
25 actuators.
13. Tree pruning apparatus according to Claim 12, wherein said actuator means are pneumatic actuator assemblies comprising a pneumatic actuator working against a spring.
- 30 14. Tree pruning apparatus according to any one of the preceding Claims, wherein said pruning assembly is driven along said elongate body member in use at a linear blade edge velocity of from 1 to 2.5 m/sec.

15. Tree pruning apparatus according to Claim 13, wherein said pneumatic actuator and spring comprise a sensor/actuator assembly, wherein said blade member is urged toward the trunk against the bias of said spring by said  
5 pneumatic actuator which is continuously operable in response to a follower interacting with the tree trunk as said sensor.

16. Tree pruning apparatus according to any one of the preceding Claims, wherein said blade members have arcuate cutting edges.  
10

17. Tree pruning apparatus according to Claim 16, wherein said cutting edges describe in combination a substantially circular cutting edge in plan.

18. Tree pruning apparatus according to Claim 16 or Claim 17, wherein said  
15 blade members are arrayed in two or more axially displaced planes, whereby said cutting edges may overlap in plan.

19. Tree pruning apparatus according to any one of the preceding Claims, wherein said blade members have a cutting edge of chisel-edged form with a  
20 substantially sheer face toward the trunk in use and a bevel from the cutting edge to the thickness of the blade body.

20. Tree pruning apparatus according to Claim 19, wherein said sheer face is relieved along said cutting edge at a relief angle of up to 6°.  
25

21. A tree pruning method including the steps of:

locating an elongate supporting body alongside the trunk of a tree to be pruned;

closing pruning jaws of a pruning assembly mounted on and drivable  
30 along said supporting body to substantially encircle the trunk, said jaws mounting a plurality of blade members having cutting edges forming a substantially circumferential array, the blade members being associated with



respective actuator means and individual sensor means associated with each actuator means and operable to dynamically maintain a selected clearance between the trunk and each said cutting edge; and

5 driving said pruning assembly along said elongate supporting body to prune said tree.

22. Tree pruning apparatus including:

an elongate supporting body locatable alongside the trunk of a tree to be pruned;

10 a pruning assembly mounted on and drivable along said supporting body and comprising a plurality of pruning jaws movable from an open position and a closed position substantially encircling the trunk;

a plurality of blade members mounted on said jaws and having cutting edges in circumferentially overlapping relation when said jaws are in their closed position;

15 actuator means associated with each said blade member; and

individual sensor means associated with each actuator means and operable to dynamically maintain a selected clearance between the trunk and each said cutting edge.

20

23. A tree pruning method including the steps of:

locating an elongate supporting body alongside the trunk of a tree to be pruned;

25 closing pruning jaws of a pruning assembly mounted on and drivable along said supporting body to substantially encircle the trunk, said jaws mounting a plurality of blade members having cutting edges in circumferentially overlapping relation, actuator means associated with each said blade member, and individual sensor means associated with each actuator means and  
30 operable to dynamically maintain a selected clearance between the trunk and each said cutting edge; and

driving said pruning assembly along said elongate supporting body to  
prune said tree.

1 / 5




FIG. 1

2 / 5




FIG. 2

3 / 5




FIG. 3

4 / 5




FIG. 4

5 / 5




FIG. 5